AIR



Modern suspended pendant for foyers and feature areas

Available in 2 sizes with 2 outputs

Opal diffuser provides a high uniform illuminance



AIR





- Available in 2 sizes with 2 outputs
- Opal diffuser provides a high uniform illuminance
- DALI dimming control gear as standard
- CRI: Ra>80
- Up to 112 lumens per Watt efficacy
- 50,000 hours lifetime (L90/B10)







Order Code	Description	lm	W	lm/W	kg
ARP930NWWD	89W - 4000K - White - Dimmable DALI	9300	89	104	5.59
ARP930NWBD	89W - 4000K - Black - Dimmable DALI	9300	89	104	5.59
ARP930NWGD	89W - 4000K - Grey - Dimmable DALI	9300	89	104	5.59
ARP1600NWWD	141W - 4000K - White - Dimmable DALI	16000	141	113	10.50
ARP1600NWBD	141W - 4000K - Black - Dimmable DALI	16000	141	113	10.50
ARP1600NWGD	141W - 4000K - Grey - Dimmable DALI	16000	141	113	10.50

Dimensions


Order Code	C (mm)	Dia.
ARP930NWWD	60	800
ARP930NWBD	60	800
ARP930NWGD	60	800
ARP1600NWWD	60	1200
ARP1600NWBD	60	1200
ARP1600NWGD	60	1200





White Option





CONSTRUCTION

- Aluminium body finished in white (RAL 9016), black (RAL 9005) or grey (RAL 9006)
- Inner Dia. 600mm or 1000mm
- Steel ceiling plate (900mm dia.) with wire suspensions (1400mm)
- Supplied as standard with neutral white (4000K) LED

OPTIONS


M3	3 hours integrated emergency
A3	Emergency self test

INSTALLATION NOTES

Suspended with 3 wire suspension kit (supplied) and powered via connection

TO SPECIFY

Large area suspended ring pendant with opal diffuser as per Tamlite Air range



Lighting for a Living





Tamlite Lighting Sales Centre

Tamlite Field Sales Centre, Park Farm Industrial Estate, Redditch, Worcestershire, B98 0HU

T. 01527 517 777 E. sales@tamlite.co.uk W. tamlite.co.uk

Over 50 years lighting for a Living

As a UK manufacturer we have one of the widest lighting ranges across:















& Leisure







Healthcare

Industrial

Office

Sports

Urban

Communal

Education

Emergency