CITY LFL



Professional linear floodlight for building facade illumination

Choice of symmetric or asymmetric distribution

RGB colour change version also available



CITY LFL





- RGB colour change version also available
- Fully adjustable for flexible install
- CRI: Ra>80
- Up to 48 lumens per Watt efficacy50,000 hours lifetime (L70/B50)








Order Code	Description	lm	W	lm/W	kg
TA2020LFL25NW	25W - 4000K	1200	25	48	2.50
TA2020LFL56NW	56W - 4000K	2300	56	41	4.40

Dimensions

Bracket

Order Code	A (mm)	B (mm)	C (mm)
TA2020LFL25NW	500	78	86
TA2020LFL56NW	1000	78	86







- Extruded aluminium body finished in grey (RAL 7031)
- 3mm tempered glass with semi-frosted finish
- Supplied with 0.5 metre H05RN 3-core, 1.0mm cable and PG-9 PVC cable gland
- Supplied as standard with neutral white (4000K) LED

OPTIONS

WW	Warm white (3000K)
CW	Cool white (5000K)
RGB	Colour change version also


Note: Additional components are required to enable RGB synchronisation, please consult our technical department for further details

INSTALLATION NOTES


Surface mount via die-cast aluminium bracket

TO SPECIFY

Wall washer floodlight as per Tamlite CITY LFL range



Lighting for a Living



Choice of symmetric or asymmetric distribution



Tamlite Lighting Sales Centre

Tamlite Field Sales Centre, Park Farm Industrial Estate, Redditch, Worcestershire, B98 0HU

T. 01527 517 777E. sales@tamlite.co.ukW. tamlite.co.uk

Over 50 years lighting for a Living

As a UK manufacturer we have one of the widest lighting ranges across:























Communal Education

n Em

Emergency

Healthcare

Industrial

Office

Retail & Leisure

Sports

Urban Warehouse & Logistics