

High quality LED light source, ideal for retail applications


Fully adjustable up to  $350^{\circ}$  rotation and  $45^{\circ}$  tilt

High performance adjustable LED downlight



Lighting for a Living





- Fully adjustable up to 350° rotation and 45° tilt
  Full range of gear options including DALI and emergency are available
- CRI: Ra>80
- Up to 97 lumens per Watt efficacy50,000 hours lifetime (L70/B50)
- Available in TamliteCRISP, TamliteWHITE and TamliteRED (see page 104)













Order Code	Description	lm	W	lm/W	kg
TMHGLED2000NW	20W - 4000K	1900	20	95	1.74
TMHGLED3000NW	30W - 4000K	2900	30	97	1.74
TMHGLED4000NW	39W - 4000K	3800	39	97	1.74

#### **Dimensions**

Order Code	C (mm)	Dia. (mm)	Cut-Out (mm)
TMHGLED2000NW	175	205	195
TMHGLED3000NW	175	205	195
TMHGLED4000NW	175	205	195





#### CONSTRUCTION

- Die-cast aluminium body finished in white (RAL 9016)
- Polished aluminium reflector
- Supplied as standard with neutral white (4000K) LED

## **OPTIONS**


RM3	3 hours remote emergency
A3	Auto self test
<u>D3</u>	DALI self test
D	DALI dimming control gear
WW	Warm white (3000K)

#### **INSTALLATION NOTES**

Recessed into plasterboard or exposed grid ceiling via spring clips

## TO SPECIFY

High output recessed adjustable downlight as per Tamlite i5 range



Lighting for a Living

# Tamlite Lighting Sales Centre

Tamlite Field Sales Centre, Park Farm Industrial Estate, Redditch, Worcestershire, B98 0HU

T. 01527 517 777E. sales@tamlite.co.ukW. tamlite.co.uk

# Over 50 years lighting for a Living

As a UK manufacturer we have one of the widest lighting ranges across:





















Communal Education

on I

Emergency

Healthcare

Industrial

Office

Retail Sports & Leisure

Urban

Warehouse & Logistics