MODLED® LG



Tamlite I-Tech diffuser designed for low glare reduction to BS EN-12464 compliance Suitable for office installations and general or task area lighting Backlit LED array for improved uniformity



MODLED® LG





- Suitable for office installations and general or task area
- Backlit LED array for improved uniformity
 Suitable for use in VDU areas such as offices, schools and universities. High output version also ideal for Retail and Commercial areas
- Gear options including DALI and emergency available
- Available with warm white (3000K), neutral white (4000K) or cool white (5000K)
- CRI: Ra>80
- Up to 130 lumens per Watt efficacy50,000 hours lifetime (L70/B50)









High performance backlit module with VDT optic


Order Code	Description	lm	W	lm/W	kg
PBL66300NW	23W - 4000K	3000	23	130	2.17
PBL66300WW	23W - 3000K	3000	23	130	2.17
PBL66300CW	23W - 5000K	3000	23	130	2.17

Dimensions

Order Code	A (mm)	B (mm)	C (mm)
PBL66300NW	595	595	35
PBL66300WW	595	595	35
PBL66300CW	595	595	35

MODLED[®] SB





CONSTRUCTION

- Extruded aluminium body finished in white (RAL 9010)
- TP(a) rated diffuser
- Backlit LED array
- Remote driver

OPTIONS


D	Dimmable DALI
M3	3 hours integrated emergency
А3	Emergency self test
D3	DALI self test

INSTALLATION NOTES

Recessed into exposed T-Bar ceiling with connection to remote driver

TO SPECIFY

High performance backlit module with VDT optic as per Tamlite MODLED LG range



Lighting for a Living







Tamlite Lighting Sales Centre

Tamlite Field Sales Centre, Park Farm Industrial Estate, Redditch, Worcestershire, B98 0HU

T. 01527 517 777E. sales@tamlite.co.ukW. tamlite.co.uk

Over 50 years lighting for a Living

As a UK manufacturer we have one of the widest lighting ranges across:























Communal Education

n Em

Emergency

Healthcare

Industrial

Office

Retail & Leisure

Sports

Urban Warehouse & Logistics