





# MODLED TP



Recessed edge-lit LED panel with flame retardant -Tp(a) opal diffuser

Modular dimensions allow easy install in most exposed T-bar ceilings

High efficiency SMD LED chips



LIAQA AWARD  
WINNER 2017



ACCREDITED  
SUPPLIER

Lighting for  
**a Living**

# MODLED TP

## LOW ENERGY LED RECESSED EDGE-LIT PANEL WITH TP(A) RATING

5 YR

IP20



### FEATURES

- > Recessed edge-lit LED panel with flame retardant -Tp(a) opal diffuser
- > High efficiency SMD LED chips
- > Modular dimensions allow easy install in most exposed T-bar ceilings
- > Remote pre-wired driver supplied
- > High performance opal diffuser for even light distribution
- > Full range of gear options including dimmable, DALI and emergency available
- > CRI: Ra>80
- > Up to 110 lumens per Watt efficacy
- > 45,000 hours expected life (L70/B50)

### CONSTRUCTION

- > Extruded aluminium frames finished in white (RAL 9016)
- > Opal PMMA diffuser
- > Multi, side-lit LED array
- > Remote driver
- > Supplied as standard with neutral white (4000K) LED

### TO SPECIFY ORDER

Recessed LED opal panel supplied with driver as per TamLite MODLED range

### INSTALLATION NOTES

Recessed lay-in for exposed 25mm ceiling grid. Brackets available for plasterboard mount. Frame available for metal pan ceilings

### OPTIONS

- HFD Digital dimmable version
- RM3 Remote maintained 3 hour emergency



## LOW ENERGY LED RECESSED EDGE-LIT PANEL

Order Code	LED	lm	W	lm/W	A (mm)	B (mm)	C (mm)	kg
MLT66340NW	31W - 4000K	3400	31	110	595	595	13	3.50



OFFICE - MODULAR DIMENSIONS ALLOW EASY  
INSTALL IN MOST EXPOSED T-BAR CEILINGS



# Contact Us

## Sales Centre

Tamlite Field Sales Centre,  
Park Farm Industrial Estate,  
Redditch, Worcestershire,  
B98 0HU

T. +44 1527 517 777  
E. [sales@tamlite.co.uk](mailto:sales@tamlite.co.uk)  
W. [tamlite.co.uk](http://tamlite.co.uk)

