

BATTEN

Integral Driver and LED Module

Steel Body in
White Finish

Available in 3
Different Lengths

Opal Diffuser

3000K
4000K
6000K

5YRS
WARRANTY



IP20

IK06

M3



- Ideal for replacement of linear fluorescent fixtures
- Suitable for general domestic and commercial use
- Available in 3 lengths
- CCTK [3000K/4000K/6000K] adjustable via simple 3-way selector switch
- Steel body in white finish
- High quality opal diffuser to reduce glare
- Integral emergency option available
- Integral high quality driver and LED module
- Loop in/out mains connector
- BESA fixings for rear or end cable entry
- Up to 141 lumens per Watt efficacy

Order Code	Description	W	lm	lm/W
XCSBT417CT	17W - 1200mm Batten CC [3000K/4000K/6000K]	17	2400	141
XCSBT528CT	28W - 1500mm Batten CC [3000K/4000K/6000K]	28	3700	132
XCSBT631CT	31W - 1800mm Batten CC [3000K/4000K/6000K]	31	4200	135
XCSBT435CT	35W - 1200mm Batten CC [3000K/4000K/6000K]	35	4300	123
XCSBT555CT	55W - 1500mm Batten CC [3000K/4000K/6000K]	55	6600	120
XCSBT660CT	60W - 1800mm Batten CC [3000K/4000K/6000K]	60	7400	123

T: +44 1527 517 777
W: xciteledlighting.co.uk
E: sales@xciteledlighting.co.uk