

BATTEN



Available with PIR [VB1T] or
PIR and Photocell [VB2T]

Steel Body in
White Finish

Available in 4
Different Lengths

Opal Diffuser

3000K
4000K
6000K

5YRS
WARRANTY



IP20

IK06

M3





- Ideal for replacement of linear fluorescent fixtures
- Suitable for general domestic and commercial use
- Available in 4 lengths
- Available with PIR [VB1T] or PIR & Photocell [VB2T]
- Steel body in white finish
- High quality opal diffuser to reduce glare
- Integral emergency option available
- Integral high quality driver and LED module
- Loop in/out mains connector
- BESA fixings for rear or end cable entry
- Up to 170 lumens per Watt efficacy

Order Code	Description	W	lm	lm/W
XCSBT417WW	17W - 1200mm Batten - 3000K	17	2050	121
XCSBT528WW	28W - 1500mm Batten - 3000K	28	3350	120
XCSBT631WW	31W - 1800mm Batten - 3000K	31	3850	124
XCSBT210NW	10W - 600mm Batten - 4000K	10	1150	115
XCSBT417NW	17W - 1200mm Batten - 4000K	17	2150	126
XCSBT435NW	35W - 1200mm Batten - 4000K	35	4000	114
XCSBT518NW	18W - 1500mm Batten - 4000K	18	2400	133
XCSBT528NW	28W - 1500mm Batten - 4000K	28	3500	125
XCSBT555NW	55W - 1500mm Batten - 4000K	55	6550	119
XCSBT631NW	31W - 1800mm Batten - 4000K	31	4050	131
XCSBT660NW	60W - 1800mm Batten - 4000K	60	7650	128
XCSBT660HONW	60W - 1800mm Batten - 4000K - High Output	60	10000	170
XCSBT528DL	28W - 1500mm Batten - 6000K	28	3500	125
XCSBT555DL	55W - 1500mm Batten - 6000K	55	6550	119
XCSBT631DL	31W - 1800mm Batten - 6000K	31	4050	131
XCSBT660DL	60W - 1800mm Batten - 6000K	60	7700	128

T: +44 1527 517 777
W: xciteledlighting.co.uk
E: sales@xciteledlighting.co.uk

xcite[®]
 LED LIGHTING