

DOWNLIGHT BL

Available in
6 Sizes

Die-cast Aluminium Body

Plug and
Play Driver



Opal Polystyrene
Diffuser

3000K
4000K

3YRS
WARRANTY



IP54

IK03



- Ideal for retrofit of existing CFL Fixtures
- Suitable for general circulation areas
- Available in 6 sizes
- Edge-lit LED array with ultra slim profile
- Die-cast aluminium body
- Opal polystyrene diffuser - TP[b]
- Plug and play driver
- 3 hours emergency maintained with compatible conversion box Emergency Kit
- Up to 104 lumens per Watt efficacy

Order Code	Description	W	lm	lm/W
XCDL4WW	4W - Downlight Low Profile IP20 - 3000K	4	300	75
XCDL4NW	4W - Downlight Low Profile IP20 - 4000K	4	350	88
XCDL4DL	4W - Downlight Low Profile IP20 - 6000K	4	350	88
XCDL8WW	8W - Downlight Low Profile IP20 - 3000K	8	600	75
XCDL8DL	8W - Downlight Low Profile IP20 - 6000K	8	650	81
XCDL8NW	8W - Downlight Low Profile IP20 - 4000K	8	650	81
XCDL12WW	12W - Downlight Low Profile IP20 - 3000K	12	1050	88
XCDL12DL	12W - Downlight Low Profile IP20 - 6000K	12	1100	92
XCDL12NW	12W - Downlight Low Profile IP20 - 4000K	12	1100	92
XCDL15WW	15W - Downlight Low Profile IP20 - 3000K	15	1300	87
XCDL15NW	15W - Downlight Low Profile IP20 - 4000K	15	1350	90
XCDL15DL	15W - Downlight Low Profile IP20 - 6000K	15	1350	104
XCDL17WW	17W - Downlight Low Profile IP20 - 3000K	17	1450	85
XCDL17DL	17W - Downlight Low Profile IP20 - 6000K	17	1650	97
XCDL17NW	17W - Downlight Low Profile IP20 - 4000K	17	1650	97
XCDL22WW	22W - Downlight Low Profile IP20 - 3000K	22	2050	93
XCDL22NW	22W - Downlight Low Profile IP20 - 4000K	22	2250	102
XCDL22DL	22W - Downlight Low Profile IP20 - 6000K	22	2250	102

T: +44 1527 517 777
W: xciteledlighting.co.uk
E: sales@xciteledlighting.co.uk

xcite[®]
 LED LIGHTING