

FRD CC



Plug and Play
Driver



30, 60 & 90 Minute
Fire Rating

5 Different Colour
Bevel Options Available

3000K
4000K
6000K

5YRS
WARRANTY



IP65

IK03

DIMMABLE





- Ideal for retrofit of existing halogen downlight fixtures
- Suitable for domestic applications
- CCTK [3000K/4000K/6000K] adjustable via simple 3-way selector switch
- Available in 5 different coloured bezels and 2 sizes [not included]
- Dimmable as standard
- Loop in/out mains connections with easy-fit connector
- Convert to larger sized cut outs with the Conversion Plates
- 30 minute fire rating with Staircraft I-Joist [Compatability Matrix]
- 30, 60 and 90 minutes fire rating with solid timber joists
- Steel body providing a high level of fire protection in accordance with Building Regulations Part B
- Up to 100 lumens per Watt efficacy

| Order Code | Description | W | Im | Im/W |
|------------|---|---|---------|------|
| XCFRA7CT | 7W - Fire Rated Recessed Downlight - IP65 - [3000K/4000K/6000K] | 7 | 600-700 | 100 |

T: +44 1527 517 777
W: xciteledlighting.co.uk
E: sales@xciteledlighting.co.uk

xcite[®]
LED LIGHTING