

MINI FLOOD

Available in 3 Different Sizes and Outputs



High Quality
Toughened
Safety Glass

Stirrup and 1m of Flex
for Column, Bracket or
Surface Fix

3000K
6000K

3YRS
WARRANTY



IP65

IK08





- Ideal for retrofit of existing halogen downlight fixtures
- Available in 3 different outputs
- Available in 3 sizes
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- Available with microwave detector
- High quality toughened safety glass
- White or black body finish
- Die-cast aluminium body
- Low energy and maintenance free solution
- Up to 75 lumens per Watt efficacy

Order Code	Description	W	lm	lm/W
XCMF10BDL	10W - Miniflood Slimline - Black - 6000K	10	600	60
XCMF10WDL	10W - Miniflood Slimline - White - 6000K	10	600	60
XCMF20BDL	20W - Miniflood Slimline - Black - 6000K	20	1500	75
XCMF20WDL	20W - Miniflood Slimline - White - 6000K	20	1500	75
XCMF30BDL	30W - Miniflood Slimline - Black - 6000K	30	2000	67
XCMF30WDL	30W - Miniflood Slimline - White - 6000K	30	2000	67
XCMF10BWW	10W - Miniflood Slimline - Black - 3000K	10	500	50
XCMF20BWW	20W - Miniflood Slimline - Black - 3000K	20	1400	70
XCMF30BWW	30W - Miniflood Slimline - Black - 3000K	30	1800	60

T: +44 1527 517 777

W: xciteledlighting.co.uk

E: sales@xciteledlighting.co.uk

xcite[®]
LED LIGHTING