

PANEL

2 Sizes Available with
2.5mm Light Guide

Compatible with
Panel Frame



Plug and Play
Driver

Extruded Aluminium
Frame

3000K
4000K
5000K
6000K

5YRS
WARRANTY



IP20

IK03



- Ideal for retrofit of existing T5 or T8 fixtures
- Suitable for offices and schools
- Backlit recessed module
- Dimmable (switch dim) versions available
- More consistent and uniform appearance than traditional edge-lit panels or downlights
- Compatible with Panel Frame
- Extruded aluminium frame

- High performance opal TP[b] diffuser
- Plug and play driver
- Supplied in neutral white [4000K], cool white [5000K] or daylight [6000K]
- Please note daylight [6000K] warm white [3000K] is only available in 600mm x 600mm
- 3 hours emergency maintained with compatible conversion box Emergency Kit
- Up to 106 lumens per Watt efficacy

Order Code	Description	W	lm	lm/W
XCBLP6630CW	30W - Recessed Backlit Panel - 600mm x 600mm - 5000K	30	3000	100
XCBLP6630WW	30W - Recessed Backlit Panel - 600mm x 600mm - 3000K	30	3000	100
XCBLP6630NW	30W - Recessed Backlit Panel - 600mm x 600mm - 4000K	30	3000	100
XCBLP6630DL	30W - Recessed Backlit Panel - 600mm x 600mm - 6000K	30	3000	100
XCBLP6630NWD	30W - Recessed Backlit Panel - 600mm x 600mm - 4000K - Dimmable	30	3000	100
XCBLP6630DLD	30W - Recessed Backlit Panel - 600mm x 600mm - 6000K - Dimmable	30	3000	100
XCBLP12650NW	50W - Recessed Backlit Panel - 1200mm x 600mm - 4000K	50	5300	106
XCBLP12650CW	50W - Recessed Backlit Panel - 1200mm x 600mm - 5000K	50	5300	106
XCBLP12650DL	50W - Recessed Backlit Panel - 1200mm x 600mm - 6000K	50	5300	106

T: +44 1527 517 777

W: xciteledlighting.co.uk

E: sales@xciteledlighting.co.uk

xcite[®]
LED LIGHTING