

PANEL

2 Sizes Available with
2.5mm Light Guide

Compatible with
Panel Frame



Plug and Play
Driver

Extruded Aluminium
Frame

3000K
4000K
5000K
6000K

3YRS
WARRANTY



IP20

IK03



- Ideal for retrofit of existing T5 or T8 fixtures
- Suitable for offices and schools
- 2 sizes available with 2.5mm light guide
- Compatible with Panel Frame
- Extruded aluminium frame
- High performance opal TP[b] diffuser
- Plug and play driver

- Emergency option available
- Supplied in neutral white [4000K], cool white [5000K] or daylight [6000K]
- Please note daylight [6000K] warm white [3000K] is only available in 600mm x 600mm
- 3 hours emergency maintained with compatible conversion box Emergency Kit
- Up to 100 lumens per Watt efficacy

Order Code	Description	W	lm	lm/W
XCRP6630NW	30W - Recessed Edge-lit Panel - 600mm x 600mm - 4000K	30	3000	100
XCRP6630WW	30W - Recessed Edge-lit Panel - 600mm x 600mm - 3000K	30	3000	100
XCRP6630CW	30W - Recessed Edge-lit Panel - 600mm x 600mm - 5000K	30	3000	100
XCRP6630DL	30W - Recessed Edge-lit Panel - 600mm x 600mm - 6000K	30	3000	100
XCRP12650NW	50W - Recessed Edge-lit Panel - 1200mm x 600mm - 4000K	30	5000	100
XCRP12650CW	50W - Recessed Edge-lit Panel - 1200mm x 600mm - 5000K	30	5000	100
XCRP12650DL	50W - Recessed Edge-lit Panel - 1200mm x 600mm - 6000K	30	5000	100

T: +44 1527 517 777
W: xciteledlighting.co.uk
E: sales@xciteledlighting.co.uk

xcite[®]
 LED LIGHTING