

Order Code: XCBLAM3STEU3

XCITE BLADE ST XCBLA 2W - 6500K - Fixed output - Emergency Self-test



Features

- Ideal for retrofit of existing emergency fixtures
- Suitable for ceiling, wall or surface fixings
- 20mm conduit rear cable entries
- Supplied with flag pole mounting kit
- Multi purpose LED emergency drop light
- Supplied with LiFePO4 battery

Construction

- Operates in maintained and non-maintained mode
- Supplied with EURO 4 running man legend
- Integral auto self-test for reduced maintenance



Technical Data

| General                       |           | Electrical                |                   |
|-------------------------------|-----------|---------------------------|-------------------|
| Luminaire Wattage (W)         | 2         | Rated Input Current (A)   | 0.04              |
| Weight (kg)                   | 0.79      | Power Factor (pf)         | 0.2               |
| Operating Temperature (ta °C) | 5° to 25° | Input Voltage Range (VAC) | 220 to 240        |
| Driver                        |           | Conductor Size (mm)       | 1.5               |
|                               |           | Terminal Type             | 4 pole screw down |
|                               |           |                           |                   |
| Driver Current (mA)           | 135       |                           |                   |
| Forward Voltage (V)           | 2.64      |                           |                   |

**Order Code:** XCBLAM3STEU3  
XCITE BLADE ST XCBLA 2W - 6500K - Fixed output - Emergency Self-test

Dimensions

|        |     |
|--------|-----|
| A (mm) | 344 |
| B (mm) | 237 |
| C (mm) | 42  |