xcite LED Lighting

Data Sheet

Order Code: WP15NW

30W - 1500mm Weatherproof - IP65 - 4000K



Features

- · Ideal for replacement of linear fluorescent fixtures
- Up to 120 lumens per watt efficacy

Construction

- Polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- Supplied as standard with neutral white [4000K] LED

Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.

Technical Data

General		Electrical	
Luminaire Wattage (W)	30	Power Factor (pf)	0.9
Weight (kg)	2.24	Input Voltage Range (VAC)	230
Light Output Lumens (Im)		Inrush Current Peak (A)	1
	3600	Surge Protection (kV)	2
Efficacy (Im/W)	120	Conductor Size (mm)	2.5
		Terminal Type	3 pole piano key
LED			
CCT (K)	4000		
Driver			
Driver Current (mA)	125		



xcite LED Lighting

Data Sheet



Order Code: WP15NW

30W - 1500mm Weatherproof - IP65 - 4000K

Dimensions

A (mm)	1575
B (mm)	67
C (mm)	73

Line Drawing



