xcite LED Lighting

Data Sheet



Order Code: WP15NWM3

30W - 1500mm Weatherproof - IP65 - 3hrs Maintained Emergency - 4000K



Features

- · Ideal for replacement of linear fluorescent fixtures
- Up to 120 lumens per watt efficacy

Construction

- · Polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- · Stainless steel fixing clips
- Supplied as standard with neutral white [4000K] LED

Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.

Technical Data

General		Electrical	
30	Power Factor (pf)	0.9	
2.38	Inrush Current Peak (A)	1	
	Surge Protection (kV)	2	
3600	Conductor Size (mm)	2.5	
120	Terminal Type	4 pole piano key	
4000			
125			
	2.38 3600 120 4000	30 Power Factor (pf) 2.38 Inrush Current Peak (A) Surge Protection (kV) Conductor Size (mm) Terminal Type 4000	



xcite LED Lighting

Data Sheet



Order Code: WP15NWM3

30W - 1500mm Weatherproof - IP65 - 3hrs Maintained Emergency - 4000K

Dimensions

A (mm)	1565
B (mm)	100
C (mm)	106

Line Drawing



