## xcite LED Lighting

### **Data Sheet**

Order Code: WP25NW

62W - 1500mm Twin Body Weatherproof - IP65 - 4000K



#### **Features**

- · Ideal for replacement of linear fluorescent fixtures
- Up to 118 lumens per watt efficacy

#### Construction

- Polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- Supplied as standard with neutral white [4000K] LED

Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.

#### **Technical Data**

General		Electrical	
Luminaire Wattage (W)	62	Power Factor (pf)	0.9
Weight (kg)	3.31	Input Voltage Range (VAC)	230
Light Output		Inrush Current Peak (A)	1
	7300	Surge Protection (kV)	2
Efficacy (Im/W)	118	Conductor Size (mm)	2.5
LED		Terminal Type	3 pole piano key
CCT (K)	4000		
Driver			
Driver Current (mA)	125		



# xcite LED Lighting

### **Data Sheet**



Order Code: WP25NW

62W - 1500mm Twin Body Weatherproof - IP65 - 4000K

#### **Dimensions**

A (mm)	1575
B (mm)	105
C (mm)	73

#### Line Drawing



