

Order Code: WP25NW

62W - 1500mm Twin Body Weatherproof - IP65 - 4000K

Features

- Ideal for replacement of linear fluorescent fixtures
- Up to 118 lumens per watt efficacy

Construction

- Polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- Supplied as standard with neutral white [4000K] LED



Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.

Technical Data

General

Luminaire Wattage (W)	62
Weight (kg)	3.31

Light Output

Lumens (lm)	7300
Efficacy (lm/W)	118

LED

CCT (K)	4000
---------	------

Driver

Driver Current (mA)	125
---------------------	-----

Electrical

Power Factor (pf)	0.9
Input Voltage Range (VAC)	230
Inrush Current Peak (A)	1
Surge Protection (kV)	2
Conductor Size (mm)	2.5
Terminal Type	3 pole piano key

Order Code: WP25NW

62W - 1500mm Twin Body Weatherproof - IP65 - 4000K

Dimensions

A (mm)	1575
B (mm)	105
C (mm)	73

Line Drawing

