

**Order Code: WP25NWM3**

62W - 1500mm Twin Body Weatherproof - IP65 - 3hrs Maintained Emergency - 4000K

**Features**

- Ideal for replacement of linear fluorescent fixtures
- Up to 118 lumens per watt efficacy

**Construction**

- Polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- Supplied as standard with neutral white [4000K] LED

Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.

**Technical Data****General**

Luminaire Wattage (W)	62
Weight (kg)	3.35

**Light Output**

Lumens (lm)	7300
Efficacy (lm/W)	118

**Electrical**

Power Factor (pf)	0.9
Inrush Current Peak (A)	1
Surge Protection (kV)	2
Conductor Size (mm)	2.5
Terminal Type	4 pole piano key

**LED**

CCT (K)	4000
---------	------

**Driver**

Driver Current (mA)	125
---------------------	-----

### Order Code: WP25NWM3

62W - 1500mm Twin Body Weatherproof - IP65 - 3hrs Maintained Emergency - 4000K

#### Dimensions

A (mm)	1565
B (mm)	155
C (mm)	106

#### Line Drawing

