

Order Code: XCBD11NWM3PC

11W - Decorative Weatherproof IP65 Bulkhead with Opal Diffuser - Photocell - 3hrs Maintained Emergency - 4000K



Features

- Ideal for retrofit of existing 2D fixtures
- Suitable for exterior use, outdoor or walkways
- Choice of plain or eyelid optic
- Up to 109 lumens per watt efficacy

Construction

- Polycarbonate body
- Opal diffuser
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED



Technical Data

| General                       |         | Electrical                |                  |
|-------------------------------|---------|---------------------------|------------------|
| Luminaire Wattage (W)         | 11      | Rated Input Current (A)   | 0.14             |
| Weight (kg)                   | 0.76    | Power Factor (pf)         | 0.9              |
| Operating Temperature (ta °C) | 5 to 25 | Input Voltage Range (VAC) | 220-240          |
| Light Output                  |         | Inrush Current Peak (A)   | 24.4             |
| Lumens (lm)                   | 1200    | Surge Protection (kV)     | 0.5              |
| Efficacy (lm/W)               | 109     | Conductor Size (mm)       | 2.5              |
| LED                           |         | Terminal Type             | 4 pole piano key |
| CCT (K)                       | 4000    |                           |                  |
| CRI                           | 80      |                           |                  |
| Macadam Ellipses              | 4       |                           |                  |
| Emergency                     |         |                           |                  |
| Emergency Lumen Operating     | 218     |                           |                  |
| Emergency Wattage (W)         | 3       |                           |                  |

**Order Code:** XCBD11NWM3PC  
11W - Decorative Weatherproof IP65 Bulkhead with Opal Diffuser - Photocell - 3hrs Maintained Emergency - 4000K

Dimensions

|           |     |
|-----------|-----|
| C (mm)    | 60  |
| Dia. (mm) | 275 |

Line Drawing

