

**Order Code: XCBDE11NWM3**

11W - Decorative Eyelid Design Bulkhead with Opal Diffuser - IP65 - 3hrs Maintained Emergency - 4000K



**Features**

- Ideal for retrofit of existing 2D fixtures
- Suitable for exterior use, outdoor or walkways
- Photocell option available
- Choice of plain or eyelid optic
- Up to 100 lumens per watt efficacy

**Construction**

- Polycarbonate body
- Opal diffuser
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED



**Technical Data**

General		Electrical	
Luminaire Wattage (W)	11	Rated Input Current (A)	0.14
Weight (kg)	0.76	Power Factor (pf)	0.9
Operating Temperature (ta °C)	5 to 25	Input Voltage Range (VAC)	220-240
Light Output		Inrush Current Peak (A)	24.4
		Surge Protection (kV)	0.5
		Conductor Size (mm)	2.5
Lumens (lm)	1100	Terminal Type	4 pole piano key
Efficacy (lm/W)	100		
<b>LED</b>			
CCT (K)	4000		
CRI	80		
Macadam Ellipses	4		
<b>Emergency</b>			
Emergency Lumen Operating	211		
Emergency Wattage (W)	3		

**Order Code: XCBDE11NWM3**

11W - Decorative Eyelid Design Bulkhead with Opal Diffuser - IP65 - 3hrs Maintained Emergency - 4000K

Dimensions

C (mm)	60
-----	
Dia. (mm)	275
-----	

Line Drawing

