

Order Code: XCBDE11NWM3PC

11W - Decorative Eyelid Design Bulkhead with Opal Diffuser - IP65 - Photocell - 3hrs Maintained Emergency - 4000K



Features

- Ideal for retrofit of existing 2D fixtures
- Suitable for exterior use, outdoor or walkways
- Photocell option available
- Choice of plain or eyelid optic
- Up to 100 lumens per watt efficacy

Construction

- Polycarbonate body
- Opal diffuser
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED



Technical Data

General	
Luminaire Wattage (W)	11
Weight (kg)	0.76
Operating Temperature (ta °C)	5 to 25
Light Output	
Lumens (lm)	1100
Efficacy (lm/W)	100
LED	
CCT (K)	4000
CRI	80
Macadam Elipses	4
Emergency	
Emergency Lumen Operating	211
Emergency Wattage (W)	3

Electrical	
Rated Input Current (A)	0.14
Power Factor (pf)	0.9
Input Voltage Range (VAC)	220-240
Inrush Current Peak (A)	24.4
Surge Protection (kV)	0.5
Conductor Size (mm)	2.5
Terminal Type	4 pole piano key

Order Code: XCBDE11NWM3PC

11W - Decorative Eyelid Design Bulkhead with Opal Diffuser - IP65 - Photocell - 3hrs Maintained Emergency - 4000K

Dimensions

C (mm)	60
Dia. (mm)	275

Line Drawing

