

Order Code: XCBDE11NWPC
11W - Decorative Eyelid Design Bulkhead with Opal Diffuser - IP65 - Photocell - 4000K



Features

- Ideal for retrofit of existing 2D fixtures
- Suitable for exterior use, outdoor or walkways
- Photocell option available
- Choice of plain or eyelid optic
- Up to 100 lumens per watt efficacy

Construction

- Polycarbonate body
- Opal diffuser
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED



Technical Data

General		Electrical	
Luminaire Wattage (W)	11	Rated Input Current (A)	0.14
Weight (kg)	0.76	Power Factor (pf)	0.9
Operating Temperature (ta °C)	-20 to 25	Input Voltage Range (VAC)	220-240
Light Output		Inrush Current Peak (A)	24.4
		Surge Protection (kV)	0.5
		Conductor Size (mm)	2.5
Lumens (lm)	1100	Terminal Type	3 pole piano key
Efficacy (lm/W)	100		
LED			
CCT (K)	4000		
CRI	80		
Macadam Elipses	4		

Order Code: XCBDE11NWPC
11W - Decorative Eyelid Design Bulkhead with Opal Diffuser - IP65 - Photocell - 4000K

Dimensions

C (mm)	60
Dia. (mm)	275

Line Drawing

