

Order Code: XCBDE11NWPC

11W - Decorative Eyelid Design Bulkhead with Opal Diffuser - IP65 - Photocell - 4000K



Features

- Ideal for retrofit of existing 2D fixtures
- Suitable for exterior use, outdoor or walkways
- Photocell option available
- Choice of plain or eyelid optic
- Up to 100 lumens per watt efficacy

Construction

- Polycarbonate body
- Opal diffuser
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED



Technical Data

| General | | Electrical | |
|-------------------------------|-----------|---------------------------|------------------|
| Luminaire Wattage (W) | 11 | Rated Input Current (A) | 0.14 |
| Weight (kg) | 0.76 | Power Factor (pf) | 0.9 |
| Operating Temperature (ta °C) | -20 to 25 | Input Voltage Range (VAC) | 220-240 |
| Light Output | | Inrush Current Peak (A) | 24.4 |
| | | Surge Protection (kV) | 0.5 |
| | | Conductor Size (mm) | 2.5 |
| Lumens (lm) | 1100 | Terminal Type | 3 pole piano key |
| Efficacy (lm/W) | 100 | | |
| LED | | | |
| CCT (K) | 4000 | | |
| CRI | 80 | | |
| Macadam Ellipses | 4 | | |

Order Code: XCBDE11NWPC

11W - Decorative Eyelid Design Bulkhead with Opal Diffuser - IP65 - Photocell - 4000K

Dimensions

| | |
|-----------|-----|
| C (mm) | 60 |
| Dia. (mm) | 275 |

Line Drawing

