

Order Code: XCBDL10NW

10W - Recessed Backlit Downlight - 4000K



Features

- Suitable for corridors, reception areas, indoor circulation spaces, retail, toilets and shower rooms
- Available in 2 different outputs
- More consistent and uniform appearance than traditional edge-lit panels or downlights
- Up to 85 lumens per watt efficacy

Construction

- Plastic housing and reflector
- Loop in/out 2-pole terminal
- Integral driver
- IP54 Rated



Technical Data

General		Electrical	
Luminaire Wattage (W)	10	Rated Input Current (A)	0.12
Weight (kg)	0.17	Power Factor (pf)	0.9
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	85-265
		Inrush Current Peak (A)	27.6
		Surge Protection (kV)	0.5
		Conductor Size (mm)	2.5
		Terminal Type	2 pole screw down
Light Output			
Lumens (lm)	850		
Efficacy (lm/W)	85		
LED			
CCT (K)	4000		
CRI	80		
Macadam Ellipses	4		

Order Code: XCBDL10NW

10W - Recessed Backlit Downlight - 4000K

Dimensions

C (mm)	82
-----	-----
Cut Out (mm)	90
-----	-----
Dia. (mm)	115
-----	-----

Line Drawing

