

**Order Code: XCBDL10WW**

10W - Recessed Backlit Downlight - 3000K



**Features**

- Suitable for corridors, reception areas, indoor circulation spaces, retail, toilets and shower rooms
- Available in 2 different outputs
- More consistent and uniform appearance than traditional edge-lit panels or downlights
- Up to 70 lumens per watt efficacy

**Construction**

- Plastic housing and reflector
- Integral driver
- Loop in/out 2-pole terminal
- IP54 Rated



**Technical Data**

General		Electrical	
Luminaire Wattage (W)	10	Rated Input Current (A)	0.12
Weight (kg)	0.17	Power Factor (pf)	0.9
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	85-265
<b>Light Output</b>		Inrush Current Peak (A)	27.6
Lumens (lm)	700	Surge Protection (kV)	0.5
Efficacy (lm/W)	70	Conductor Size (mm)	2.5
<b>LED</b>		Terminal Type	2 pole screw down
CCT (K)	3000		
CRI	80		
Macadam Ellipses	4		

**Order Code:** XCBDL10WW

10W - Recessed Backlit Downlight - 3000K

### Dimensions

C (mm)	82
-----	
Cut Out (mm)	90
-----	
Dia. (mm)	115
-----	

### Line Drawing

