

**Order Code: XCBDL20WW**

20W - Recessed Backlit Downlight - 3000K



**Features**

- Suitable for corridors, reception areas, indoor circulation spaces, retail, toilets and shower rooms
- Available in 2 different outputs
- More consistent and uniform appearance than traditional edge-lit panels or downlights
- Up to 95 lumens per watt efficacy

**Construction**

- Plastic housing and reflector
- Integral driver
- Loop in/out 2-pole terminal
- IP54 Rated



**Technical Data**

| General                       |         | Electrical                |                   |
|-------------------------------|---------|---------------------------|-------------------|
| Luminaire Wattage (W)         | 20      | Rated Input Current (A)   | 0.23              |
| Weight (kg)                   | 0.55    | Power Factor (pf)         | 0.9               |
| Operating Temperature (ta °C) | 0 to 25 | Input Voltage Range (VAC) | 85-265            |
| <b>Light Output</b>           |         | Inrush Current Peak (A)   | 55.2              |
| Lumens (lm)                   | 1900    | Surge Protection (kV)     | 0.5               |
| Efficacy (lm/W)               | 95      | Conductor Size (mm)       | 2.5               |
| <b>LED</b>                    |         | Terminal Type             | 2 pole screw down |
| CCT (K)                       | 3000    |                           |                   |
| CRI                           | 80      |                           |                   |
| Macadam Elipses               | 4       |                           |                   |

**Order Code: XCBDL20WW**

20W - Recessed Backlit Downlight - 3000K

### Dimensions

|              |       |
|--------------|-------|
| C (mm)       | 130   |
| -----        | ----- |
| Cut Out (mm) | 200   |
| -----        | ----- |
| Dia. (mm)    | 240   |
| -----        | ----- |

### Line Drawing

