xcite LED Lighting
Data Sheet

Order Code: XCBDL20WW

20W - Recessed Backlit Downlight - 3000K



Features

- Suitable for corridors, reception areas, indoor circulation spaces, retail, toilets and shower rooms
- Available in 2 different outputs
- More consistent and uniform appearance than traditional edge-lit panels or downlights
- Up to 95 lumens per watt efficacy

Construction

- Plastic housing and reflector
- Integral driver
- Loop in/out 2-pole terminal
- IP54 Rated



Technical Data

General

Luminaire Wattage (W)	20
Weight (kg)	0.55
Operating Temperature (ta °C)	0 to 25

Light Output

Lumens (lm)	1900
Efficacy (lm/W)	95

LED

CCT (K)	3000
CRI	80
Macadam Elipses	4

Electrical

Rated Input Current (A)	0.23
Power Factor (pf)	0.9
Input Voltage Range (VAC)	85-265
Inrush Current Peak (A)	55.2
Surge Protection (kV)	0.5
Conductor Size (mm)	2.5
Terminal Type	2 pole screw down

Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk

xcite LED Lighting

Data Sheet

Order Code: XCBDL20WW

20W - Recessed Backlit Downlight - 3000K

Dimensions

Height (mm)	130
Cut Out (mm)	200
Dia. (mm)	240

Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk