
xcite LED Lighting

Data Sheet



Order Code: XCBH12CTM3GT

XCITE RETRO FIT GEAR TRAY XCBH 14W - Fixed output - Emergency - 3000K-6500K



Features

- CCT [3000K/4000K/6500K] adjustable via 3-way selector switch
- Microwave movement sensor available
- Up to 148 lumens per watt efficacy

Construction

Emergency option available

Installation Notes

Universal fitting suitable for various circular enclosures















Technical Data

General		
Luminaire Wattage (W)	14.2	F
Weight (kg)	0.38	F
Operating Temperature (ta °C)		I
Light Output		ا
Lumens (Im)	2100	
Efficacy (Im/W)	4.40	
LED		
CRI	80	
Macadam Elipses	3	
Driver		
Driver Current (mA)	350	
Forward Voltage (V)	32.6	
Emergency		
Emergency Lumen Operating	155	
Emergency Wattage (W)	1	

Electrical	
Rated Input Current (A)	0.09
Power Factor (pf)	0.72
Input Voltage Range (VAC)	198 - 264
Inrush Current Peak (A)	292
Surge Protection (kV)	1 kV
Conductor Size (mm)	0.5 to 2.5
Terminal Type	SLK series 4 to pole grip to wire



xcite LED Lighting

Data Sheet



Order Code: XCBH12CTM3GT

XCITE RETRO FIT GEAR TRAY XCBH 14W - Fixed output - Emergency - 3000K-6500K

Dimensions

C (mm)	40
Dia. (mm)	265

Line Drawing

