

Order Code: XCBH12CTM3GT

XCITE RETRO FIT GEAR TRAY XCBH 14W - Fixed output - Emergency - 3000K-6500K



Features

- CCT selectable via selector switch [3000K/4000K/6500K]
- Microwave movement sensor available
- Up to 148 lumens per watt efficacy

Construction

- Emergency option available

Installation Notes

Universal fitting suitable for various circular enclosures



Technical Data

| General | | Electrical | |
|-------------------------------|-------------------|---------------------------|-----------------------------------|
| Luminaire Wattage (W) | 14.2 | Rated Input Current (A) | 0.09 |
| Weight (kg) | 0.38 | Power Factor (pf) | 0.72 |
| Operating Temperature (ta °C) | 0 to 25 | Input Voltage Range (VAC) | 198 - 264 |
| | | Inrush Current Peak (A) | 292 |
| | | Surge Protection (kV) | 1 kV |
| | | Conductor Size (mm) | 0.5 to 2.5 |
| | | Terminal Type | SLK series 4 to pole grip to wire |
| Light Output | | | |
| Lumens (lm) | 2100 | | |
| Efficacy (lm/W) | 148 | | |
| LED | | | |
| CCT (K) | 3000K/4000K/6500K | | |
| CRI | 80 | | |
| Macadam Ellipses | 3 | | |
| Driver | | | |
| Driver Current (mA) | 350 | | |
| Forward Voltage (V) | 32.6 | | |
| Emergency | | | |
| Emergency Lumen Operating | 155 | | |
| Emergency Wattage (W) | 1 | | |

Order Code: XCBH12CTM3GT

XCITE RETRO FIT GEAR TRAY XCBH 14W - Fixed output - Emergency - 3000K-6500K

Dimensions

| | |
|-----------|-----|
| C (mm) | 40 |
| Dia. (mm) | 265 |

Line Drawing

