

**Order Code: XCBH12CTM3HFSPC**

12W - Circular Bulkhead - IP65 - Microwave Sensor - 3hrs Maintained Emergency - CCTK Selector [3000K/4000K/6000K] - Polished Chrome

**Features**

- Ideal for retrofit of existing 2D fixtures
- Suitable for bathrooms or storerooms
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- Microwave movement sensor available
- Up to 92 lumens per watt efficacy

**Construction**

- Polycarbonate body
- Polished Chrome finish available
- Integral emergency option available

**Technical Data****General**

Luminaire Wattage (W)	12
Weight (kg)	1.20
Operating Temperature (ta °C)	5 to 25

**Light Output**

Lumens (lm)	1000-1100
Efficacy (lm/W)	92

**LED**

CCT (K)	TRI-COLOUR
CRI	80
Macadam Ellipses	4

**Emergency**

Emergency Lumen Operating	140
Emergency Wattage (W)	2

**Electrical**

Rated Input Current (A)	0.07
Power Factor (pf)	0.7
Input Voltage Range (VAC)	220-240
Inrush Current Peak (A)	10
Surge Protection (kV)	1
Conductor Size (mm)	2.5
Terminal Type	4 pole screw down

**Order Code: XCBH12CTM3HFSPC**

12W - Circular Bulkhead - IP65 - Microwave Sensor - 3hrs Maintained Emergency - CCTK Selector [3000K/4000K/6000K] - Polished Chrome

Dimensions

C (mm)	110
Dia. (mm)	330

Line Drawing

