

**Order Code: XCBH12CTM3PC**

12W - Circular Bulkhead - IP65 - 3hr Maintained Emergency - CCTK Selector [3000K/4000K/6000K] - Polished Chrome



**Features**

- Ideal for retrofit of existing 2D fixtures
- Suitable for bathrooms or storerooms
- Microwave movement sensor available
- CCT adjustable via selector switch [3000K/4000K/6000K]
- Up to 92 lumens per watt efficacy

**Construction**

- Polycarbonate body
- Polished Chrome finish available
- Integral emergency option available



**Technical Data**

General		Electrical	
Luminaire Wattage (W)	12	Rated Input Current (A)	0.07
Weight (kg)	1.15	Power Factor (pf)	0.7
Operating Temperature (ta °C)	5 to 25	Input Voltage Range (VAC)	220-240
<b>Light Output</b>		Inrush Current Peak (A)	10
Lumens (lm)	1000 to 1100	Surge Protection (kV)	1
Efficacy (lm/W)	92	Conductor Size (mm)	2.5
<b>LED</b>		Terminal Type	4 pole screw down
CCT (K)	3000K/4000K/6000K		
CRI	80		
Macadam Ellipses	4		
<b>Emergency</b>			
Emergency Lumen Operating	140		
Emergency Wattage (W)	2		

**Order Code:** XCBH12CTM3PC

12W - Circular Bulkhead - IP65 - 3hr Maintained Emergency - CCTK Selector [3000K/4000K/6000K] - Polished Chrome

### Dimensions

C (mm)	110
Dia. (mm)	330

### Line Drawing

