

Order Code: XCBH12CTPC
12W - Circular Bulkhead - IP65 - CCTK Selector [3000K/4000K/6000K] - Polished Chrome



Features

- Ideal for retrofit of existing 2D fixtures
- Suitable for bathrooms or storerooms
- Microwave movement sensor available
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- Up to 92 lumens per watt efficacy

Construction

- Polycarbonate body
- Polished Chrome finish available
- Integral emergency option available



Technical Data

| General                       |            | Electrical                |                  |
|-------------------------------|------------|---------------------------|------------------|
| Luminaire Wattage (W)         | 12         | Rated Input Current (A)   | 0.07             |
| Weight (kg)                   | 0.85       | Power Factor (pf)         | 0.7              |
| Operating Temperature (ta °C) | 0 to 25    | Input Voltage Range (VAC) | 220-240          |
| Light Output                  |            | Inrush Current Peak (A)   | 10               |
| Lumens (lm)                   | 1000-1100  | Surge Protection (kV)     | 1                |
| Efficacy (lm/W)               | 92         | Conductor Size (mm)       | 2.5              |
| LED                           |            | Terminal Type             | 3 pole piano key |
| CCT (K)                       | TRI-COLOUR |                           |                  |
| CRI                           | 80         |                           |                  |
| Macadam Elipses               | 4          |                           |                  |

**Order Code:** XCBH12CTPC  
12W - Circular Bulkhead - IP65 - CCTK Selector [3000K/4000K/6000K] - Polished Chrome

Dimensions

|           |     |
|-----------|-----|
| C (mm)    | 110 |
| Dia. (mm) | 330 |

Line Drawing

