# xcite LED Lighting

## **Data Sheet**



Order Code: XCBHC6

6W - Bulkhead Wall Light with Opal Polycarbonate Diffuser - IP65 - 6000K - Black



#### **Features**

- Suitable for exterior walls and entrance areas
- Photocell option available
- Up to 67 lumens per watt efficacy

#### Construction

- High quality polycarbonate construction
- Black polycarbonate body
- Shallow profile diffuser
- Opal polycarbonate diffuser
- Supplied with daylight [6000K]















### **Technical Data**

General		
Luminaire Wattage (W)	6	Rated Input
Weight (kg)	0.38	Power Facto
Operating Temperature (ta °C)	0.4.05	Input Voltage
Light Output  Lumens (Im)		Inrush Curre
	400	Surge Prote
Efficacy (lm/W)	67	Conductor S
		Terminal Typ
LED		
CCT (K)	6000	
CRI	80	
Macadam Elipses	4	

Electrical		
Rated Input Current (A)	0.05	
Power Factor (pf)	0.5	
Input Voltage Range (VAC)	220-240	
Inrush Current Peak (A)	25	
Surge Protection (kV)	1	
Conductor Size (mm)	2.5	
Terminal Type	3 pole piano key	

# xcite LED Lighting

# **Data Sheet**



Order Code: XCBHC6

6W - Bulkhead Wall Light with Opal Polycarbonate Diffuser - IP65 - 6000K - Black

### **Dimensions**

A (mm)	245
B (mm)	125
C (mm)	97

### Line Drawing



