

Order Code: XCBHCBOX1M3

X1 Bulkhead WP - Circular - Opal diffuser - CCT [3000K/4000K/6000K] + Wattage Selectable - Black - Emergency



Features

- Suitable for exterior commercial and industrial applications
- Wattage [8W,10W,12W] adjustable via 3-way selector switch
- CCT adjustable via 3-way selector switch [3000K/4000K/6000K]

Construction

- Modular [emergency](#) and [microwave sensor](#)'s available for quick and easy conversion of a standard fitting
- For additional control, please use [X1 Bulkhead Remote](#) [Sold Separately]

Installation Notes

3-point screw fixing
 Conduit side entry points for surface mount cable entry
 Loop-in, loop-out push-fit terminal block for quick tool-free installation



Technical Data

General

Luminaire Wattage (W)	8W/12W/16W
Weight (kg)	0.81
Operating Temperature (ta °C)	5° to 25°

Light Output

Lumens (lm)	1070 to 1930
Efficacy (lm/W)	128

LED

CCT (K)	3000K/4000K/6000K
CRI	80
Macadam Elipses	1 to 1.5

Driver

Driver Current (mA)	140/215/280
Forward Voltage (V)	48.5 to 52.5

Emergency

Emergency Lumen Operating	146
Emergency Wattage (W)	2

Electrical

Rated Input Current (A)	0.04 to 0.08
Power Factor (pf)	0.83 to 0.92
Input Voltage Range (VAC)	198 to 264
Inrush Current Peak (A)	19.1
Surge Protection (kV)	1
Conductor Size (mm)	0.5 to 2.5
Terminal Type	4 pole piano key

Order Code: XCBHCBOX1M3

X1 Bulkhead WP - Circular - Opal diffuser - CCT [3000K/4000K/6000K] + Wattage Selectable - Black - Emergency

Dimensions

C (mm)	85

Dia. (mm)	282

Line Drawing

