

**Order Code: XCBHCWPX1M3**

Prismatic diffuser - 3000K-6000K + Wattage Selectable - White - Emergency

**Technical Data****General**

Luminaire Wattage (W)	8W/12W/16W
Weight (kg)	0.81
Operating Temperature (ta °C)	5° to 25°

**Light Output**

Lumens (lm)	1200 to 2120
Efficacy (lm/W)	155

**LED**

CCT (K)	3000K to 6000K
CRI	80
Macadam Ellipses	0.9 to 1.4

**Driver**

Driver Current (mA)	140/215/280
Forward Voltage (V)	48.5 to 52.5

**Emergency**

Emergency Lumen Operating	146
Emergency Wattage (W)	2

**Features**

- Suitable for exterior commercial and industrial applications
- Wattage [8W,10W,12W] adjustable via 3-way selector switch
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch

**Construction**

- Modular [emergency](#) and [microwave sensor](#)'s available for quick and easy conversion of a standard fitting
- For additional control, please use [X1 Bulkhead Remote](#) [Sold Separately]

**Installation Notes**

3-point screw fixing  
Conduit side entry points for surface mount cable entry  
Loop-in, loop-out push-fit terminal block for quick tool-free instalation

### Order Code: XCBHCWPX1M3

Prismatic diffuser - 3000K-6000K + Wattage Selectable - White - Emergency

#### Dimensions

C (mm)	85
Dia. (mm)	282

#### Line Drawing

