xcite LED Lighting

Data Sheet



Order Code: XCBHCWPX1M3

Prismatic diffuser - 3000K-6000K + Wattage Selectable - White - Emergency



Features

- Suitable for exterior commercial and industrial applications
- Wattage [8W,10W,12W] adjustable via 3-way selector switch
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch

Construction

- Modular emergency and microwave sensor's available for quick and easy conversion of a standard fitting
- For additional control, please use X1 Bulkhead Remote [Sold Separately]

Installation Notes

3-point screw fixing Conduit side entry points for surface mount cable entry Loop-in, loop-out push-fit terminal block for quick tool-free instalation























Technical Data

General		Electrical	
Luminaire Wattage (W)	8W/12W/16W	Rated Input Current (A)	0.04 to 0.08
Weight (kg)	0.81	Power Factor (pf)	0.82 to 0.92
Operating Temperature (ta °C)	5° to 25°	Input Voltage Range (VAC)	198 to 264
Light Output Lumens (Im)		Inrush Current Peak (A)	2.08
	1200-2120	Surge Protection (kV)	1
Efficacy (Im/W)	155	Conductor Size (mm)	0.5 to 2.5
Lineady (iii)		Terminal Type	4 pole piano key
LED			
CRI	80		
Macadam Elipses	0.9 to 1.4		
Driver			
Driver Current (mA)	140/215/280		
Forward Voltage (V)	48.5 to 52.5		
Emergency			
Emergency Lumen Operating	146		
Emergency Wattage (W)	2		

xcite LED Lighting

Data Sheet



Order Code: XCBHCWPX1M3

Prismatic diffuser - 3000K-6000K + Wattage Selectable - White - Emergency

Dimensions

C (mm)	85
Dia. (mm)	282

Line Drawing



