

Order Code: XCBHSWOX1

Opal diffuser - 3000K-6000K + Wattage Selectable - White

**Technical Data****General**

Luminaire Wattage (W)	8W/12W/16W
Weight (kg)	0.71
Operating Temperature (ta °C)	0° to 25°

Light Output

Lumens (lm)	1100 to 2000
Efficacy (lm/W)	141

LED

CRI	80
Macadam Ellipses	1.0 to 1.6

Driver

Driver Current (mA)	140/215/280
Forward Voltage (V)	48.5 to 52.5

Features

- Suitable for exterior commercial and industrial applications
- Wattage [8W,10W,12W] adjustable via 3-way selector switch
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch

Construction

- Modular [emergency](#) and [microwave sensor](#)'s available for quick and easy conversion of a standard fitting
- For additional control, please use [X1 Bulkhead Remote](#) [Sold Separately]

Installation Notes

4-point screw fixing
Conduit side entry points for surface mount cable entry
Loop-in, loop-out push-fit terminal block for quick tool-free instalation

Order Code: XCBHSWOX1

Opal diffuser - 3000K-6000K + Wattage Selectable - White

Dimensions

A (mm)	252
B (mm)	252
C (mm)	92

Line Drawing

