

Order Code: XCBHSWOX1M3MS

Opal diffuser - 3000K-6000K + Wattage Selectable - White - Emergency - Microwave sensor

**Technical Data****General**

| | |
|-------------------------------|------------|
| Luminaire Wattage (W) | 8W/12W/16W |
| Weight (kg) | 0.84 |
| Operating Temperature (ta °C) | 5° to 25° |

Light Output

| | |
|-----------------|--------------|
| Lumens (lm) | 1100 to 2000 |
| Efficacy (lm/W) | 141 |

LED

| | |
|------------------|------------|
| CRI | 80 |
| Macadam Ellipses | 1.0 to 1.6 |

Driver

| | |
|---------------------|--------------|
| Driver Current (mA) | 140/215/280 |
| Forward Voltage (V) | 48.5 to 52.5 |

Emergency

| | |
|---------------------------|-----|
| Emergency Lumen Operating | 146 |
| Emergency Wattage (W) | 2 |

Features

- Suitable for exterior commercial and industrial applications
- Wattage [8W,10W,12W] adjustable via 3-way selector switch
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch

Construction

- Modular [emergency](#) and [microwave sensor](#)'s available for quick and easy conversion of a standard fitting
- For additional control, please use [X1 Bulkhead Remote](#) [Sold Separately]

Installation Notes

4-point screw fixing
Conduit side entry points for surface mount cable entry
Loop-in, loop-out push-fit terminal block for quick tool-free instalation

Order Code: XCBHSWOX1M3MS

Opal diffuser - 3000K-6000K + Wattage Selectable - White - Emergency - Microwave sensor

Dimensions

| | |
|--------|-----|
| A (mm) | 252 |
| B (mm) | 252 |
| C (mm) | 92 |

Line Drawing

