xcite LED Lighting

Data Sheet



0.07 0.85 220-240


2.5

4 pole screw down

Order Code: XCBHWPCBOM3HFS

16W - Circular Bulkhead with Opal Diffuser - IP65 - 3hrs Maintained Emergency - 4000K - Black Base - Microwave Sensor







Construction

- High quality polycarbonate construction
- Polycarbonate body
- White base or black base available
- Opal or prismatic diffuser available
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED



















Technical Data

rediffical Data		
General		Electrical
Luminaire Wattage (W)	16	Rated Input Current (A)
Weight (kg)	1.18	Power Factor (pf)
Operating Temperature (ta °C)	5 to 25	Input Voltage Range (VAC)
Light Output Lumens (Im)		Inrush Current Peak (A)
	1500	Surge Protection (kV)
Efficacy (Im/W)	94	Conductor Size (mm)
		Terminal Type
LED		
CCT (K)	4000	
CRI	80	
Macadam Elipses	4	
Emergency		
Emergency Lumen Operating	210	
Emergency Wattage (W)	2	



xcite LED Lighting

Data Sheet



Order Code: XCBHWPCBOM3HFS

16W - Circular Bulkhead with Opal Diffuser - IP65 - 3hrs Maintained Emergency - 4000K - Black Base - Microwave Sensor

Dimensions

C (mm)	85
Dia. (mm)	282

Line Drawing

