xcite LED Lighting

Data Sheet



Order Code: XCBHWPCBPM3

16W - Circular Bulkhead with Prismatic Diffuser - IP65 - 3hrs Maintained Emergency - 4000K - Black Base

Features





- Construction
- Polycarbonate body
- White base or black base available

• Up to 113 lumens per watt efficacy

- High quality polycarbonate construction
- Opal or prismatic diffuser available
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED

















Technical Data

| General | | |
|-------------------------------|---------|--|
| Luminaire Wattage (W) | 16 | |
| Weight (kg) | 1 1/ | |
| Operating Temperature (ta °C) | 5 to 25 | |
| Light Output | | |
| Lumens (Im) | 1800 | |
| Efficacy (Im/W) | 113 | |
| LED | | |
| CCT (K) | 4000 | |
| CRI | 80 | |
| Macadam Elipses | 4 | |
| Emergency | | |
| Emergency Lumen Operating | 236 | |
| Emergency Wattage (W) | 2 | |

| Electrical | |
|---------------------------|-------------------|
| Rated Input Current (A) | 0.07 |
| Power Factor (pf) | 0.85 |
| Input Voltage Range (VAC) | 220-240 |
| Inrush Current Peak (A) | 10 |
| Surge Protection (kV) | 1 |
| Conductor Size (mm) | 2.5 |
| Terminal Type | 4 pole screw down |

xcite LED Lighting

Data Sheet



Order Code: XCBHWPCBPM3

16W - Circular Bulkhead with Prismatic Diffuser - IP65 - 3hrs Maintained Emergency - 4000K - Black Base

Dimensions

| C (mm) | 85 |
|-----------|-----|
| Dia. (mm) | 282 |

Line Drawing



