xcite LED Lighting

Data Sheet



Order Code: XCBHWPCWOM3HFS

16W - Circular Bulkhead with Opal Diffuser - IP65 - 3hrs Maintained Emergency - 4000K - White Base - Microwave Sensor Features



- Suitable for general interior or exterior use
- 20mm conduit side cable entries for wall or ceiling fix
- Up to 94 lumens per watt efficacy

Construction

- Polycarbonate body
- White base or black base available
- High quality polycarbonate construction
- Opal or prismatic diffuser available
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED

















Technical Data

Toolinda Data		ai Bata
General		
Luminaire Wattage (W)	16	Rated Input Current (A)
Weight (kg)	1.18	Power Factor (pf)
Operating Temperature (ta °C)	5 to 25	Input Voltage Range (VAC)
Light Output Lumens (Im)		Inrush Current Peak (A)
	1500	Surge Protection (kV)
Efficacy (Im/W)	94	Conductor Size (mm)
Lineacy (III)		Terminal Type
LED		
CCT (K)	4000	
CRI	80	
Macadam Elipses	4	
Emergency		
Emergency Lumen Operating	210	
Emergency Wattage (W)	2	

Electrical		
Rated Input Current (A)	0.07	
Power Factor (pf)	0.85	
Input Voltage Range (VAC)	220-240	
Inrush Current Peak (A)	10	
Surge Protection (kV)	1	
Conductor Size (mm)	2.5	
Terminal Type	4 pole screw down	

xcite LED Lighting

Data Sheet



Order Code: XCBHWPCWOM3HFS

16W - Circular Bulkhead with Opal Diffuser - IP65 - 3hrs Maintained Emergency - 4000K - White Base - Microwave Sensor

Dimensions

C (mm)	85
Dia. (mm)	282

Line Drawing

