xcite LED Lighting

Data Sheet



Order Code: XCBHWPCWP

16W - Circular Bulkhead with Prismatic Diffuser - IP65 - 4000K - White Base



Features

- Suitable for general interior or exterior use
- 20mm conduit side cable entries for wall or ceiling fix
- Up to 113 lumens per watt efficacy

Construction

- High quality polycarbonate construction
- Polycarbonate body
- White base or black base available
- Opal or prismatic diffuser available
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED

















Technical Data

General		
Luminaire Wattage (W)	16	
Weight (kg)	0.82	
Operating Temperature (ta °C)	0 to 25	
Light Output		
Lumens (Im)	1800	
Efficacy (lm/W)	113	
LED		
CCT (K)	4000	
CRI	80	
Macadam Elipses	1	
Driver		
Driver Current (mA)	240	
Forward Voltage (V)	54-64	

Electrical	
Rated Input Current (A)	0.07
Power Factor (pf)	0.9
Input Voltage Range (VAC)	220-240
Inrush Current Peak (A)	10
Surge Protection (kV)	1
Conductor Size (mm)	2.5
Terminal Type	3 pole piano key

xcite LED Lighting

Data Sheet



Order Code: XCBHWPCWP

16W - Circular Bulkhead with Prismatic Diffuser - IP65 - 4000K - White Base

Dimensions

C (mm)	85
Dia. (mm)	282

Line Drawing



