# xcite LED Lighting

## **Data Sheet**



0.07

220-240

2.5

3 pole piano key

### Order Code: XCBHWPCWPHFS

16W - Circular Bulkhead with Prismatic Diffuser - IP65 - 4000K - White Base - Microwave Sensor

### **Features**



- 20mm conduit side cable entries for wall or ceiling fix
- Up to 113 lumens per watt efficacy

### Construction

- High quality polycarbonate construction
- Polycarbonate body
- White base or black base available
- Opal or prismatic diffuser available
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED



















### **Technical Data**

	Technic	ai Dala	
General Luminaire Wattage (W)	16	Rated Input Current (A)	Electrical
Weight (kg)	0.86	Power Factor (pf)	
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	
Light Output	ut	Inrush Current Peak (A)	
Lumens (Im)	1800	Surge Protection (kV)	
Efficacy (lm/W)	113	Conductor Size (mm) Terminal Type	
LED			
CCT (K)	4000		
CRI	80		
Macadam Elipses	4		
Driver			
Driver Current (mA)	240		
Forward Voltage (V)	54-64		



# xcite LED Lighting

# **Data Sheet**



## Order Code: XCBHWPCWPHFS

16W - Circular Bulkhead with Prismatic Diffuser - IP65 - 4000K - White Base - Microwave Sensor

### **Dimensions**

C (mm)	85
Dia. (mm)	282

### Line Drawing

