

Order Code: XCBHWPCWPM3HFS

16W - Circular Bulkhead with Prismatic Diffuser - IP65 - 3hrs Maintained Emergency - 4000K - White Base - Microwave Sensor

Features

- Suitable for general interior or exterior use
- 20mm conduit side cable entries for wall or ceiling fix
- Up to 113 lumens per watt efficacy

Construction

- High quality polycarbonate construction
- Polycarbonate body
- White base or black base available
- Opal or prismatic diffuser available
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED

**Technical Data****General**

| | |
|-------------------------------|---------|
| Luminaire Wattage (W) | 16 |
| Weight (kg) | 1.18 |
| Operating Temperature (ta °C) | 5 to 25 |

Light Output

| | |
|-----------------|------|
| Lumens (lm) | 1800 |
| Efficacy (lm/W) | 113 |

LED

| | |
|------------------|------|
| CCT (K) | 4000 |
| CRI | 80 |
| Macadam Ellipses | 4 |

Emergency

| | |
|---------------------------|-----|
| Emergency Lumen Operating | 236 |
| Emergency Wattage (W) | 2 |

Electrical

| | |
|---------------------------|-------------------|
| Rated Input Current (A) | 0.07 |
| Power Factor (pf) | 0.85 |
| Input Voltage Range (VAC) | 220-240 |
| Inrush Current Peak (A) | 10 |
| Surge Protection (kV) | 1 |
| Conductor Size (mm) | 2.5 |
| Terminal Type | 4 pole screw down |

Order Code: XCBHWPCWPM3HFS

16W - Circular Bulkhead with Prismatic Diffuser - IP65 - 3hrs Maintained Emergency - 4000K - White Base - Microwave Sensor

Dimensions

| | |
|-----------|-----|
| C (mm) | 85 |
| Dia. (mm) | 282 |

Line Drawing

