# xcite LED Lighting

## **Data Sheet**



Order Code: XCBHWPSBO

16W - Square Bulkhead with Opal diffuser - IP65 - 4000K - Black Base



### **Features**

- Suitable for general interior or exterior use
- 20mm conduit side cable entries for wall or ceiling fix
- Up to 94 lumens per watt efficacy

#### Construction

- Polycarbonate body
- White base or black base available
- High quality polycarbonate construction
- · Opal or prismatic diffuser available
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED

















## Technical Data

General	
Luminaire Wattage (W)	16
Weight (kg)	0.86
Operating Temperature (ta °C)	0 to 25
Light Output	
Lumens (Im)	1500
Efficacy (Im/W)	94
LED	
CCT (K)	4000
CRI	00
Macadam Elipses	4
Driver	
Driver Current (mA)	240
Forward Voltage (V)	54-64

Electrical	
Rated Input Current (A)	0.07
Power Factor (pf)	0.9
Input Voltage Range (VAC)	220-240
Inrush Current Peak (A)	10
Surge Protection (kV)	1
Conductor Size (mm)	2.5
Terminal Type	3 pole piano key

# xcite LED Lighting

# **Data Sheet**



### Order Code: XCBHWPSBO

16W - Square Bulkhead with Opal diffuser - IP65 - 4000K - Black Base

#### **Dimensions**

A (mm)	256
B (mm)	256
C (mm)	93

### Line Drawing



