xcite LED Lighting

Data Sheet



Order Code: XCBHWPSBO

16W - Square Bulkhead with Opal diffuser - IP65 - 4000K - Black Base



Features

- Suitable for general interior or exterior use
- 20mm conduit side cable entries for wall or ceiling fix
- Up to 94 lumens per watt efficacy

Construction

- High quality polycarbonate construction
- Polycarbonate body
- White base or black base available
- Opal or prismatic diffuser available
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED

















Technical Data

Conoral		
General		
Luminaire Wattage (W)	16	
Weight (kg)	0.86	_ [
Operating Temperature (ta °C)	0 to 25	_ [
Light Output		
Lumens (Im)	1500	
Efficacy (lm/W)	94	
LED		
CCT (K)	4000	
CRI	80	
Macadam Elipses	4	
Driver		
Driver Current (mA)	240	
Forward Voltage (V)	54-64	

Electrical	
Rated Input Current (A)	0.07
Power Factor (pf)	0.9
Input Voltage Range (VAC)	220-240
Inrush Current Peak (A)	10
Surge Protection (kV)	1
Conductor Size (mm)	2.5
Terminal Type	3 pole piano key

xcite LED Lighting

Data Sheet



Order Code: XCBHWPSBO

16W - Square Bulkhead with Opal diffuser - IP65 - 4000K - Black Base

Dimensions

A (mm)	256
B (mm)	256
C (mm)	93

Line Drawing



