

**Order Code: XCBHWPSBOM3**

16W - Square Bulkhead with Opal diffuser - IP65 - 3hrs Maintained Emergency - 4000K - Black Base



**Features**

- Suitable for general interior or exterior use
- 20mm conduit side cable entries for wall or ceiling fix
- Up to 94 lumens per watt efficacy

**Construction**

- High quality polycarbonate construction
- Polycarbonate body
- White base or black base available
- Opal or prismatic diffuser available
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED



**Technical Data**

| General                       |         | Electrical                |                   |
|-------------------------------|---------|---------------------------|-------------------|
| Luminaire Wattage (W)         | 16      | Rated Input Current (A)   | 0.07              |
| Weight (kg)                   | 1.18    | Power Factor (pf)         | 0.85              |
| Operating Temperature (ta °C) | 5 to 25 | Input Voltage Range (VAC) | 220-240           |
| <b>Light Output</b>           |         | Inrush Current Peak (A)   | 10                |
| Lumens (lm)                   | 1500    | Surge Protection (kV)     | 1                 |
| Efficacy (lm/W)               | 94      | Conductor Size (mm)       | 2.5               |
| <b>LED</b>                    |         | Terminal Type             | 4 pole screw down |
| CCT (K)                       | 4000    |                           |                   |
| CRI                           | 80      |                           |                   |
| Macadam Ellipses              | 4       |                           |                   |
| <b>Emergency</b>              |         |                           |                   |
| Emergency Lumen Operating     | 210     |                           |                   |
| Emergency Wattage (W)         | 2       |                           |                   |

**Order Code: XCBHWPSBOM3**

16W - Square Bulkhead with Opal diffuser - IP65 - 3hrs Maintained Emergency - 4000K - Black Base

Dimensions

|        |     |
|--------|-----|
| A (mm) | 256 |
| B (mm) | 256 |
| C (mm) | 93  |

Line Drawing

