

Order Code: XCBHWPSBP

16W - Square Bulkhead with Prismatic diffuser - IP65 - 4000K - Black Base



Features

- Suitable for general interior or exterior use
- 20mm conduit side cable entries for wall or ceiling fix
- Up to 113 lumens per watt efficacy

Construction

- High quality polycarbonate construction
- Polycarbonate body
- White base or black base available
- Opal or prismatic diffuser available
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED



Technical Data

| General | | Electrical | |
|-------------------------------|---------|---------------------------|------------------|
| Luminaire Wattage (W) | 16 | Rated Input Current (A) | 0.07 |
| Weight (kg) | 0.86 | Power Factor (pf) | 0.9 |
| Operating Temperature (ta °C) | 0 to 25 | Input Voltage Range (VAC) | 220-240 |
| | | Inrush Current Peak (A) | 10 |
| | | Surge Protection (kV) | 1 |
| | | Conductor Size (mm) | 2.5 |
| | | Terminal Type | 3 pole piano key |
| Light Output | | | |
| Lumens (lm) | 1800 | | |
| Efficacy (lm/W) | 113 | | |
| LED | | | |
| CCT (K) | 4000 | | |
| CRI | 80 | | |
| Macadam Ellipses | 4 | | |
| Driver | | | |
| Driver Current (mA) | 240 | | |
| Forward Voltage (V) | 54-64 | | |

Order Code: XCBHWPSBP

16W - Square Bulkhead with Prismatic diffuser - IP65 - 4000K - Black Base

Dimensions

| | |
|--------|-----|
| A (mm) | 256 |
| B (mm) | 256 |
| C (mm) | 93 |

Line Drawing

