xcite LED Lighting

Data Sheet



0.07

220-240

2.5

3 pole piano key

Order Code: XCBHWPSBPHFS

16W - Square Bulkhead with Prismatic diffuser - IP65 - 4000K - Black Base - Microwave Sensor



Features

- Suitable for general interior or exterior use
- 20mm conduit side cable entries for wall or ceiling fix
- Up to 113 lumens per watt efficacy

Construction

- High quality polycarbonate construction
- Polycarbonate body
- White base or black base available
- Opal or prismatic diffuser available
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED

















Technical Data

recimical Data			
General			Electrical
Luminaire Wattage (W)	16	Rated Input Current (A)	
Weight (kg)	0.90	Power Factor (pf)	
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	
Light Output		Inrush Current Peak (A)	
Light Output Lumens (Im)	1800	Surge Protection (kV)	
Efficacy (lm/W)	113	Conductor Size (mm)	
LED		Terminal Type	
CCT (K)	4000		
CRI	80		
Macadam Elipses	4		
Driver			
Driver Current (mA)	240		
Forward Voltage (V)	54-64		



xcite LED Lighting

Data Sheet



Order Code: XCBHWPSBPHFS

16W - Square Bulkhead with Prismatic diffuser - IP65 - 4000K - Black Base - Microwave Sensor

Dimensions

A (mm)	256
B (mm)	256
C (mm)	91

Line Drawing



