# xcite LED Lighting

## **Data Sheet**



### Order Code: XCBHWPSWOHFS

16W - Square Bulkhead with Opal diffuser - IP65 - 4000K - White Base - Microwave Sensor



### **Features**

- Suitable for general interior or exterior use
- 20mm conduit side cable entries for wall or ceiling fix
- Up to 94 lumens per watt efficacy

### Construction

- High quality polycarbonate construction
- Polycarbonate body
- White base or black base available
- Opal or prismatic diffuser available
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED

















### **Technical Data**

		7 d. 2 d. d.
General		
Luminaire Wattage (W)	16	Rated Input Current (A)
Weight (kg)	0.90	Power Factor (pf)
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)
Light Output	Inrush Current Peak (A)	
Light Output Lumens (lm)	1500	Surge Protection (kV)
Efficacy (Im/W)	94	Conductor Size (mm)
		Terminal Type
LED		
CCT (K)	4000	
CRI	80	
Macadam Elipses	4	
Driver		
Driver Current (mA)	240	
Forward Voltage (V)	54-64	

Electrical		
Rated Input Current (A)	0.07	
Power Factor (pf)	0.9	
Input Voltage Range (VAC)	220-240	
Inrush Current Peak (A)	10	
Surge Protection (kV)	1	
Conductor Size (mm)	2.5	
Terminal Type	3 pole piano key	

# xcite LED Lighting

## **Data Sheet**



### Order Code: XCBHWPSWOHFS

16W - Square Bulkhead with Opal diffuser - IP65 - 4000K - White Base - Microwave Sensor

### **Dimensions**

A (mm)	256
B (mm)	256
C (mm)	91

### Line Drawing



